



CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

1 — 2 Ton
2TTB012 - 024

*Split System
Cooling*

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTB0012A1000B	200/230/1/60	12,000
2TTB0018A1000B	200/230/1/60	18,000
2TTB0024A1000B	208/230/1/60	24,000

Features:

- Climatuff® compressor
- All Aluminum **Spine Fin™** coil
- Polystate gray cabinet
- Full coil protection
- Corrosion resistant finish and fasteners
- Internal high/low pressure & temperature protection
- Liquid line filter-drier
- Single side service access
- Multi-use liquid and suction line service valves
- HCFC-22 refrigerant
- **5 year limited warranty on compressor**
- S.E.E.T design testing
- 100% Line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 40°F with EDC accessory AY28X079
- Low ambient cooling to 30°F with EDC accessory AY28X079 and TXV





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

2-1/2 — 5 Ton
2TTB0030 - 060A

**Split System
Cooling**

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTB0030A1000B	200/230/1/60	30,000
2TTB0036A1000B	200/230/1/60	36,000
2TTB0042A1000B	200/230/1/60	42,000
2TTB0048A1000B	200/230/1/60	48,000
2TTB0060A1000B	200/230/1/60	60,000

Features:

- Climatuff® compressor
- All aluminum Spine Fin™ coil
- DuraTuff™ base, fast complete drain, weather proof
- New appearance with polystate gray cabinet
- Quick-Sess™ cabinet, service access and refrigerant connections with full coil protection
- Corrosion resistant finish and fasteners
- Internal high/low pressure & temperature protection
- Liquid line filter-drier
- Easy single side service
- Multi-use liquid and suction line service valves
- Easy top & fan removal
- Full length control cover
- SureFast™ seams louver panel removal
- HCFC-22 refrigerant
- 5 Year limited warranty on compressor, coil, and 1 year on parts
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 40°F with EDC accessory AY28X079
- Low ambient cooling to 30°F with EDC accessory AY28X079 and TXV





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

1-1/2 — 5 Ton
2TTB3018 - 060A

XB 13
Split System
Cooling

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTB3018A1000A	200/230/1/60	17,000
2TTB3024A1000A	200/230/1/60	23,000
2TTB3030A1000A	200/230/1/60	28,500
2TTB3036A1000A	208/230/1/60	34,500
2TTB3042A1000A	200/230/1/60	40,500
2TTB3048A1000A	200/230/1/60	46,500
2TTB3060A1000A	208/230/1/60	58,500

Features:

- Climatuff® compressor
- Efficiency up to 13.25 SEER
- All aluminum Spine Fin™ coil
- WeatherGuard™ fasteners
- Quick-Sess™ cabinet, easy service access and refrigerant connections with full coil protection
- DuraTuff™ base, fast complete drain, weather proof
- Comfort"R"™ mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- 018, 024, 030, 042, 048 & 060 ship with start kit
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap
- R-22 refrigerant
- 5-year limited warranty on compressor, coil, and 5-years on internal functional parts (Residential Use)
- Extended warranties available
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

1-1/2 — 5 Ton
4TTB3018 - 060B

XB 13
Split System
Cooling **R-410**

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
4TTB3018A1000A	200/230/1/60	17,000
4TTB3024A1000A	200/230/1/60	23,000
4TTB3030A1000A	200/230/1/60	28,500
4TTB3036A1000A	208/230/1/60	34,500
4TTB3042A1000A	208/230/1/60	40,500
4TTB3048A1000A	208/230/1/60	46,500
4TTB3060B1000A	208/230/1/60	58,500

Features:

- **Climatuff®** compressor
- Efficiency up to 13.25 SEER
- All aluminum **Spine Fin™** coil
- **WeatherGuard™** fasteners
- **Quick-Sess™** cabinet, easy service access and refrigerant connections with full coil protection
- **DuraTuff™** base, fast complete drain, weather proof

- **Comfort"R"™** mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- 018, 024, 030 & 060 ship with start kit
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap

- High pressure switch
- R-410A refrigerant
- **5-year limited warranty on compressor, coil, and 5-years on internal functional parts (Residential Use)**
- **Extended warranties available**
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

1-1/2 — 5 Ton
4 TTR4018 - 060A

XR 14
Split System
Cooling

R-410

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
4TTR4018B1000A	200/230/1/60	18,000
4TTR4024B1000A	200/230/1/60	24,000
4TTR4030B1000A	208/230/1/60	30,000
4TTR4036B1000A	208/230/1/60	36,000
4TTR4042B1000A	208/230/1/60	42,000
4TTR4048B1000A	208/230/1/60	48,000
4TTR4060B1000A	208/230/1/60	60,000

Features:

- **Climatuff®** compressor
- Efficiency up to 14.00 SEER
- All aluminum **Spine Fin™** coil
- **DuraTuff™** base, fast complete drain, weather proof
- **WeatherGuard™** fasteners
- Tarpaulin gray cabinet with anthracite gray badge and cap
- Compressor sound insulator
- **Quick-Sess™** cabinet, easy service access and refrigerant connections with full coil protection
- Glossy corrosion resistant finish
- Internal high/low pressure & temperature protection
- 018, 024 & 060 ship with start kit
- Liquid line filter-drier
- **Comfort"R"™** mode approved
- Easy top & fan removal
- Full length control and service valve cover
- R-410 refrigerant
- **10 year limited warranty on compressor, coil, 5 years internal functional parts (Residential use)**
- **Extended warranties available**
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 40°F with EDC accessory AY28X079
- Low ambient cooling to 30°F with EDC accessory AY28X079 and TXV





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

2-1/2 — 5 Ton
2TTZ9030 - 060C

XL19i
Communicating

Split System
Cooling

SUSTITUYE
2TTZ90 - A/B

Specifications: 1 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTZ9030C1000A	200-230/1/60	30,000
2TTZ9036C1000A	200-230/1/60	36,000
2TTZ9048C1000A	200-230/1/60	48,000
2TTZ9060C1000A	200-230/1/60	60,000

Features:

- Two Climatuff® compressors
- Efficiency up to 19.5 SEER
- All aluminum Spine Fin™ coil
- WeatherGuard™ II top shields unit
- WeatherGuard™ fasteners
- Quick-Sess™ cabinet, service access and refrigerant connections with full coil protection
- Dura Tuff™ base, fast complete drain, weather proof

- Comfort-R™ mode approved
- ComfortLink™ II system, only two wire control connection
- Charge Assist™ fast/accurate charging every time
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Start kit standard
- 50% or 100% capacity modulation

- Compressor sump heat
- Liquid line filter/drier
- Tarpaulin gray cabinet with anthracite gray top
- Low sound with advanced fan system and compressor sound insulator
- Variable speed fan motor
- Electronic compressor control
- XL Seacoast shield
- Service valve cover
- R-22 refrigerant
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- 10-year limited warranty on compressor, coil, and internal functional parts (Residential Use)
- Extended warranties available





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

2-1/2 — 6 Ton
2TTA0030 - 072A

**Split System
Cooling
Three Phase**

Specifications: 3 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTA0030A3000A	200-230/3/60	30,000
2TTA0036A3000A	200-230/3/60	36,000
2TTA0042A3000A	200-230/3/60	42,000
2TTA0048A3000A	200-230/3/60	48,000
2TTA0060A3000A	200-230/3/60	60,000
2TTA0072A3000A	200-230/3/60	72,000
<hr/>		
2TTA0030A4000A	460/3/60	30,000
2TTA0036A4000A	460/3/60	36,000
2TTA0042A4000A	460/3/60	42,000
2TTA0048A4000A	460/3/60	48,000
2TTA0060A4000A	460/3/60	60,000
2TTA0072A4000A	460/3/60	72,000

Features:

- **Climatuff®** compressor
- All aluminum **Spine Fin™** coil
- **WeatherGuard™** fasteners
- **Quick-Sess™** cabinet, service access and refrigerant connections with full coil protection
- **DuraTuff™** base, fast complete drain, weather proof

- **Comfort"R"™** mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Compressor sump heat
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap
- Low pressure switch

- R-22 refrigerant
- **5-year limited warranty on compressor, coil, and internal functional parts (Residential Use Only)**
- **5-year limited warranty on compressor, coil, and 1 year on parts (Commercial Use Only)**
- **Extended warranties available**
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

2-1/2 — 5 Ton
2TTA3030 - 060

**Split System
Cooling
Three Phase**

Specifications: 3 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
2TTA3030A3000A	200-230/3/60	30,000
2TTA3036A3000A	200-230/3/60	36,000
2TTA3042A3000B	200-230/3/60	42,000
2TTA3048A3000A	200-230/3/60	48,000
2TTA3060A3000A	200-230/3/60	60,000
<hr/>		
2TTA3030A4000A	460/3/60	30,000
2TTA3036A4000A	460/3/60	36,000
2TTA3042A4000B	460/3/60	42,000
2TTA3048A4000A	460/3/60	48,000
2TTA3060A4000A	460/3/60	60,000

© 1999 Trane, Inc. All rights reserved.

Features:

- **Climatuff®** compressor
- All aluminum **Spine Fin™** coil
- **WeatherGuard™** fasteners
- **Quick-Sess™** cabinet, service access and refrigerant connections with full coil protection
- **DuraTuff™** base, fast complete drain, weather proof

- **Comfort'R™** mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Compressor Sump Heat
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap
- Low pressure switch

- R-22 refrigerant
- **5-year limited warranty on compressor, coil, and internal functional parts (Residential Use Only)**
- **5-year limited warranty on compressor, coil, and 1 year on parts (Commercial Use Only)**
- **Extended warranties available**
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

2-1/2 — 5 Ton
4TTA3030 - 060B

**Split System
Cooling
Three Phase** **R-410**

Specifications: 3 Phase

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)
4TTA3030A3000A	200-230/3/60	30,000
4TTA3036A3000A	200-230/3/60	36,000
4TTA3042A3000A	200-230/3/60	42,000
4TTA3048A3000A	200-230/3/60	48,000
4TTA3060B3000A	200-230/3/60	60,000
4TTA3030A4000A	460/3/60	30,000
4TTA3036A4000A	460/3/60	36,000
4TTA3042A4000A	460/3/60	42,000
4TTA3048A4000A	460/3/60	48,000
4TTA3060B4000A	460/3/60	60,000

Features:

- Climatuff® compressor
- All aluminum Spine Fin™ coil
- WeatherGuard™ fasteners
- Quick-Sess™ cabinet, service access and refrigerant connections with full coil protection
- DuraTuff™ base, fast complete drain, weather proof

- Comfort"R"™ mode approved
- Glossy corrosion resistant finish
- Internal compressor high/low pressure & temperature protection
- Liquid line filter-drier
- Polyslate gray cabinet with anthracite gray badge & cap
- R-410A refrigerant
- Low pressure switch
- High pressure switch

- Compressor sump heat
- 5-year limited warranty on compressor, coil, and internal functional parts (Residential Use Only)
- 5-year limited warranty on compressor, coil, and 1 year on parts (Commercial Use Only)
- Extended warranties available
- S.E.E.T. design testing
- 100% line run test
- Low ambient cooling to 55°F as shipped
- Low ambient cooling to 30°F with AY28X079
- Low ambient cooling to 0°F with BAYLOAM103





CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

7-1/2 — 10 Ton
TTA090 - 120A

**Split System
Cooling**

Specifications: Single Compressor

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)
TTA090A300F	—	208-230/3/60	92,000
TTA090A30SF	R-22, Epoxy Coil	208-230/3/60	92,000
TTA120A300F	—	208-230/3/60	128,000
TTA120A30SF	R-22, Epoxy Coil	208-230/3/60	128,000
TTA090A400F	—	460/3/60	92,000
TTA090A40SF	R-22, Epoxy Coil	460/3/60	92,000
TTA120A400F	—	460/3/60	128,000
TTA120A40SF	R-22, Epoxy Coil	460/3/60	128,000

Features:

- (1) Trane 3-D® Scroll compressor
- Single point power supply
- Compressor motor overload protection
- Control transformer
- High and low pressure cut-out switches
- Liquid line filter drier, factory installed
- Service valves with pressure taps
- Holding charge of Nitrogen
- Copper tube, aluminum plate fin coils
- Low ambient cooling to 50°F as manufactured
- Low ambient cooling to 0°F with accessory head pressure control
- Mounting/lifting rails under base
- Optional factory installed Black Epoxy Coil for corrosive resistance
- UL listed and CSA certified
- **5-year compressor warranty**



CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

10 — 20 Ton
TTA120 - 240B

**Split System
Cooling**

Specifications: *Dual Compressor With Dual Refrigerant Circuits*

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)
TTA120B300E	—	208-230/3/60	126,000
TTA120B30SE	R-22, Epoxy Coil	208-230/3/60	126,000
TTA150B300E	—	208-230/3/60	148,000
TTA150B30SE	R-22, Epoxy Coil	208-230/3/60	148,000
TTA180B300F	—	208-230/3/60	182,000
TTA180B30SF	R-22, Epoxy Coil	208-230/3/60	182,000
TTA240B300F	—	208-230/3/60	246,000
TTA240B30SF	R-22, Epoxy Coil	208-230/3/60	246,000
TTA120B400E	—	460/3/60	126,000
TTA120B40SE	R-22, Epoxy Coil	460/3/60	126,000
TTA150B400E	—	460/3/60	148,000
TTA150B40SE	R-22, Epoxy Coil	460/3/60	148,000
TTA180B400F	—	460/3/60	182,000
TTA180B40SF	R-22, Epoxy Coil	460/3/60	182,000
TTA240B400F	—	460/3/60	246,000
TTA240B40SF	R-22, Epoxy Coil	460/3/60	246,000

Features:

- (TTA120-180C) scroll compressors
- Single point power supply
- Compressor motor overload protection
- Control transformer
- High and low pressure cut-out switches
- Internal pressure relief valve
- Liquid line filter drier, factory installed
- Service valves with pressure taps
- Holding charge of Nitrogen
- Copper tube, aluminum plate fin coils
- Low ambient cooling to 50°F as manufactured, 0° with accessory head pressure control
- Mounting/lifting rails under base
- Optional factory installed Black Epoxy Coil for corrosive resistance
- UL listed and CSA certified
- 5-year compressor warranty (TTA120-180B,C)
- Standard compressor warranty for TTA240B is 1-year



CONDENSADORAS SOLO FRIO

It's Hard To Stop A Trane.®

10 — 20 Ton
TTA120 - 180C

**Split System
Cooling**

Specifications: Dual Manifolder Compressors with Single Refrigerant Circuit

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)
TTA120C300G	—	208-230/3/60	126,000
TTA120C30SG	R-22, Epoxy Coil	208-230/3/60	126,000
TTA180C300G	—	208-230/3/60	182,000
TTA180C30SG	R-22, Epoxy Coil	208-230/3/60	182,000
TTA120C400G	—	460/3/60	126,000
TTA120C40SG	R-22, Epoxy Coil	460/3/60	126,000
TTA180C400G	—	460/3/60	182,000
TTA180C40SG	R-22, Epoxy Coil	460/3/60	182,000

Features:

- (TTA120-180C) scroll compressors
- Single point power supply
- Compressor motor overload protection
- Control transformer
- High and low pressure cut-out switches
- Internal pressure relief valve
- Liquid line filter drier, factory installed
- Service valves with pressure taps
- Holding charge of Nitrogen
- Copper tube, aluminum plate fin coils
- Low ambient cooling to 50°F as manufactured, 0° with accessory head pressure control
- Mounting/lifting rails under base
- Optional factory installed Black Epoxy Coil for corrosive resistance
- UL listed and CSA certified
- **5-year compressor warranty (TTA120-180B,C)**
- **Standard compressor warranty for TTA240B is 1-year**

