PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

Model Nomenclature Packaged Units

4 W C Y 4 0 4 8 A 3 0 0 0 A A

Refrigerant
2 = R-22
4 = R-410A

Type
YC = Gas Electric
WC = Heat Pump
DC = Dual Fuel
TC = Air Conditioner

Model Tier
C = Entry Level
X = Upgrade
Y = Premium
Z = Leadership (2-Stage)

Efficiency Tier
3 = 13 SEER
4 = 14 SEER
6 = 16 SEER

Capacity

018	042
024	048
030	060
036	

Major Model Sequence

Voltage & Phase
1 = 230V 1-Phase
3 = 230V 3-Phase
4 = 460V 3-Phase

Gas Heat Input (MBTU/H)
000 (AC or HP)

040	096
064	120
075	

Minor Design Sequence

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

2 — 5 Ton
2YCC3024-60A

XB13c Convertible Pkg. Gas/Electric

Specifications: XB13c - Single Phase R-22

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH)
2YCC3024A1040A	208-230/1/60	23,000	32,000
2YCC3024A1064A	208-230/1/60	23,000	51,200
2YCC3030A1040A	208-230/1/60	28,000	32,000
2YCC3030A1064A	208-230/1/60	28,000	51,200
2YCC3030A1075A	208-230/1/60	28,000	60,000
2YCC3036A1064A	208-230/1/60	35,000	51,200
2YCC3036A1075A	208-230/1/60	35,000	60,000
2YCC3036A1096A	208-230/1/60	35,000	76,800
2YCC3042A1064A	208-230/1/60	40,000	51,200
2YCC3042A1075A	208-230/1/60	40,000	60,000
2YCC3042A1096A	208-230/1/60	40,000	76,800
2YCC3048A1075A	208-230/1/60	47,000	60,000
2YCC3048A1096A	208-230/1/60	47,000	76,800
2YCC3048A1120A	208-230/1/60	47,000	96,000
2YCC3060A1096A	208-230/1/60	58,000	76,800
2YCC3060A1120A	208-230/1/60	58,000	96,000

Features:

- All steel louvers and cabinet for rugged, long lasting protection
- Weather Beater Top contoured for great appearance and reinforced for strength
- Stainless steel burners and heat exchanger for extra long life and safety
- Quiet operation delivers great in-home comfort with minimal sound
- Appliance grade finish of durable powder paint baked on both sides of the panels
- Exclusive **Climatuff®** high efficiency compressor with internal overload protection
- High efficiency outdoor fan motor for quiet and reliable operation
- Copper tube, aluminum fin indoor coil
- Semi-Elliptical Logarighmic Expansion Composite **Vortica®** blower provides better airflow and less sound while using less energy
- **Spine Fin™** outdoor coil for long lasting performance and durability
- Right side electrical service access for high and low voltage connections
- Rugged steel basepan features deep drawn duct connections and emergency drains
- Steeply sloped composite drainpan
- Ships in horizontal configuration and converts quickly for downflow
- Optional filter rack kits fit inside the unit. Available for 1" or 2" media
- Non-bleed expansion valves on indoor and outdoor coils
- Direct drive multi-speed indoor blower motors
- Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment
- Standard operation to 55°F as manufactured
- Low ambient cooling to 0°F with kit
- UL approved and listed
- **10-year heat exchanger, 5-year compressor and other parts limited warranty (Residential Use Only)**
- **Optional extended warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

1-1/2 — 5 Ton
4YCC3018-60A

XB13c Convertible Pkg. Gas/Electric

R-410

Specifications: XB13c - Single Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH)
4YCC3018A1040A	208-230/1/60	18,000	32,000
4YCC3036A1064A	208-230/1/60	35,000	51,200
4YCC3036A1075A	208-230/1/60	35,000	60,000
4YCC3036A1096A	208-230/1/60	35,000	76,800
4YCC3048A1075A	208-230/1/60	46,500	60,000
4YCC3048A1096A	208-230/1/60	46,500	76,800
4YCC3048A1120A	208-230/1/60	46,500	96,000
4YCC3060A1096A	208-230/1/60	58,000	76,800
4YCC3060A1120A	208-230/1/60	58,000	96,000

Specifications: XB13c - Three Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH)
4YCC3036A3064A	208-230/3/60	35,000	51,200
4YCC3036A3075A	208-230/3/60	35,000	60,000
4YCC3036A3096A	208-230/3/60	35,000	76,800
4YCC3048A3075A	208-230/3/60	46,500	60,000
4YCC3048A3096A	208-230/3/60	46,500	76,800
4YCC3048A3120A	208-230/3/60	46,500	96,000
4YCC3060A3096A	208-230/3/60	58,000	76,800
4YCC3060A3120A	208-230/3/60	58,000	96,000
4YCC3036A4064A	460/3/60	35,000	51,200
4YCC3036A4075A	460/3/60	35,000	60,000
4YCC3036A4096A	460/3/60	35,000	76,800
4YCC3048A4075A	460/3/60	46,500	60,000
4YCC3048A4096A	460/3/60	46,500	76,800
4YCC3048A4120A	460/3/60	46,500	96,000
4YCC3060A4096A	460/3/60	58,000	76,800
4YCC3060A4120A	460/3/60	58,000	96,000

Features:

- All steel louvers and cabinet for rugged, long lasting protection
- Weather Beater Top contoured for great appearance and reinforced for strength
- Stainless steel burners and heat exchanger for extra long life and safety
- Quiet operation delivers great in-home comfort with minimal sound
- Appliance grade finish of durable powder paint baked on both sides of the panels
- Exclusive **Climatuff®** high efficiency compressor with internal overload protection
- High efficiency outdoor fan motor for quiet and reliable operation
- Semi-Elliptical Logarithmic Expansion Composite **Vortica®** blower provides better airflow and less sound while using less energy
- **Spine Fin™** outdoor coil for long lasting performance and durability
- Right side electrical service access for high and low voltage connections
- Rugged steel basepan features deep drawn duct connections and emergency drains
- Steeply sloped composite drainpan
- Ships in horizontal configuration and converts quickly for downflow
- Optional filter rack kits fit inside the unit. Available for 1" or 2" media
- Non-bleed expansion valves on indoor and outdoor coils
- Direct drive multi-speed indoor blower motors
- Copper tube, aluminum fan indoor coil
- Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment
- Standard operation to 55°F as manufactured
- Low ambient cooling to 0°F with kit
- UL approved and listed
- **10-year heat exchanger, 5-year compressor and other parts limited warranty (Residential Use Only)**
- **Optional extended warranty**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

2 — 5 Ton
4YCY4024-60A

XL14c
Convertible Pkg.
Gas/Electric

R-410

Specifications: XL14c - Single Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH) (1st Stg./2nd Stg.)
4YCY4024A1064AA	208-230/1/60	24,000	38,400/51,200
4YCY4036A1075AA	208-230/1/60	36,400	45,000/60,000
4YCY4036A1096AA	208-230/1/60	36,400	57,600/76,800
4YCY4048A1096AA	208-230/1/60	48,000	57,600/76,800
4YCY4048A1120AA	208-230/1/60	48,000	72,000/96,000
4YCY4060A1120AA	208-230/1/60	59,500	72,000/96,000

Specifications: XL14c - Three Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH) (1st Stg./2nd Stg.)
4YCY4036A3075AA	208-230/3/60	36,400	45,000/60,000
4YCY4036A3096AA	208-230/3/60	36,400	57,600/76,800
4YCY4048A3096AA	208-230/3/60	48,000	57,600/76,800
4YCY4048A3120AA	208-230/3/60	48,000	72,000/96,000
4YCY4060A3120AA	208-230/3/60	59,500	72,000/96,000

Features:

- Architecturally integrated louvers and corner guards deliver durable protection, extra safety, and great looks
- Weather Beater Top contoured for great appearance and reinforced for strength
- Ultra quiet operation provides best-in-class performance with barely noticeable sound levels
- Appliance grade finish of durable powder paint baked on both sides of the panels
- Exclusive **Climatuff®** high efficiency compressor with internal overload protection
- Ducted outdoor fan with a high efficiency motor for quiet and reliable operation
- Semi-Elliptical, Logarithmic Expansion Composite **Vortica®** blower provides better airflow and less sound while using less energy
- High efficiency variable speed ECM indoor blower motors with **Comfort-R™** airflow system
- **Spine Fin™** outdoor coil for long lasting performance and durability
- Right side electrical service access for high and low voltage connections
- Rugged steel basepan features deep drawn duct connections and emergency drains
- Steeply sloped composite drainpan
- Ships in horizontal configuration and converts quickly for downflow
- Optional filter rack kits fit inside the unit. Available for 1" or 2" media
- Non-bleed expansion valves on indoor coils
- Copper tube, aluminum fin indoor coil
- Stainless steel heat exchanger and burners for longer life and added safety
- Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment
- Low ambient cooling to 0°F with kit
- UL approved and listed
- **20-year heat exchanger, 10-year compressor, 10-year outdoor coil, and 5-year other parts limited warranty (Residential Use Only)**
- **Optional extended warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

3 — 5 Ton
4YCZ6036 - 60A

XL16c
Convertible Pkg.
Gas/Electric

R-410

Specifications: XL16c - Single Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH)
4YCZ6036A1075AA	208/230/1/60	35,600	56,250/75,000
4YCZ6036A1096AA	208/230/1/60	35,600	72,000/96,000
4YCZ6048A1096AA	208/230/1/60	48,000	72,000/96,000
4YCZ6048A1120AA	208/230/1/60	48,000	90,000/120,000
4YCZ6060A1120AA	208/230/1/60	57,500	90,000/120,000

Specifications: XL16c - Three Phase R-410A

Model Number	Power Supply	Capacity Cooling (BTUH)	Capacity Htg.Output (BTUH)
4YCZ6036A3075AA	208/230/3/60	35,600	56,250/75,000
4YCZ6036A3096AA	208/230/3/60	35,600	72,000/96,000
4YCZ6048A3096AA	208/230/3/60	48,000	72,000/96,000
4YCZ6048A3120AA	208/230/3/60	48,000	90,000/120,000
4YCZ6060A3120AA	208/230/3/60	57,500	90,000/120,000
4YCZ6036A4075AA	460/3/60	35,600	56,250/75,000
4YCZ6036A4096AA	460/3/60	35,600	72,000/96,000
4YCZ6048A4075AA	460/3/60	48,000	72,000/96,000
4YCZ6048A4120AA	460/3/60	48,000	90,000/120,000
4YCZ6060A4120AA	460/3/60	57,500	90,000/120,000

Features:

- Architecturally integrated louvers and corner guards deliver durable protection, extra safety, and great looks
- Weather Beater Top contoured for great appearance and reinforced for strength
- Ultra quiet operation provides best-in-class performance with barely noticeable sound levels
- Appliance grade finish of durable powder paint baked on both sides of the panels
- Exclusive **Climatuff®** high efficiency 2-stage compressor with internal overload protection
- 2-stage heating and cooling
- Stainless steel heat exchanger and burners for longer life and added safety
- Ducted outdoor fan with a high efficiency motor for quiet and reliable operation
- Semi-Elliptical, Logarithmic Expansion Composite **Vortica®** blower provides better airflow and less sound while using less energy
- High efficiency variable speed ECM indoor blower motors with **Comfort-R™** airflow system
- **Spine Fin™** outdoor coil for long lasting performance and durability
- Right side electrical service access for high and low voltage connections
- Rugged steel basepan features deep drawn duct connections and emergency drains
- Steeply sloped composite drainpan
- Copper tube, aluminum fin indoor coil
- High efficiency outdoor fan motor with polarized plug
- Shipped for horizontal application, easily convertible to downflow
- Optional filter rack kits fit inside the unit. Available for 1" or 2" media
- Non-bleed expansion valves on indoor coils
- Pressure taps, including liquid line taps, easily accessed and protected inside compressor compartment
- Low ambient cooling to 0°F with kit
- UL approved and listed
- **20-year heat exchanger, 10-year compressor, 10-year outdoor coil, and 5-year other parts limited warranty (Residential Use Only)**
- **Optional extended warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

Model Nomenclature

Precedent™ Convertible Pkg. Gas/Electric

Y	S	C	036	A	3	R	B	A	**	C	0	0	0	A	1	0	0	0	1	A	1
1	2	3	4,5,6	7	8	9	10	11	12,13	14	15	16	17	18	19	20	21	22	23	24	25

DIGIT 1 - Unit Function
T = DX Cooling
Y = DX Cooling, Gas Heat

DIGIT 2 - Efficiency
S = Standard Efficiency
H = High Efficiency

DIGIT 3 - Airflow
C = Convertible

DIGITS 4,5,6 - Nominal Gross Cooling Capacity (MBh)
033/036 = 3 Ton
043/048 = 4 Ton
060/063 = 5 Ton
072 = 6 Ton
090 = 7.5 Ton, Single Compressor
092 = 7.5 Ton, Dual Compressors
102 = 8.5 Ton
120 = 10 Ton

DIGIT 7 - Major Design Sequence
A = R-22 Refrigerant

DIGIT 8 - Unit Voltage
3 = 208-230/3/60
4 = 460/3/60
W = 575/3/60
K = 380/3/60

DIGIT 9 - Unit Controls
E = Electromechanical
R = ReliaTel™ Microprocessor

DIGIT 10 - Heating Capacity

Note: *Sequence may be any letter A through Z, or any digit 1 through 9.*
0 = No Electric Heater
B = 6 kw (3 phase)
C = 9 kw (3 phase)
E = 12 kw (3 phase)
G = 18 kw (3 phase)
J = 23 kw (3 phase)
K = 27 kw (3 phase)
N = 36 kw (3 phase)
P = 54 kw (3 phase)

Note: *Applicable to Digit 1, Y models only.*
L = Low
M = Medium
H = High
X = Low, Stainless Steel Heat Exchanger
Y = Medium, Stainless Steel Heat Exchanger
Z = High, Stainless Steel Heat Exchanger

DIGIT 11 - Minor Design Sequence
A = First Sequence

DIGIT 12,13 - Service Sequence
** = Factory Assigned

DIGIT 14 - Fresh Air Selection
0 = No Fresh Air
A = Manual Outside Air Damper 0-50%⑬
B = Motorized Outside Air Damper 0-50%
C = Economizer, Dry Bulb 0-100% without Barometric Relief②
D = Economizer, Dry Bulb 0-100% with Barometric Relief②
E = Economizer, Reference Enthalpy 0-100% without Barometric Relief①②
F = Economizer, Reference Enthalpy 0-100% with Barometric Relief①②
G = Economizer, Comparative Enthalpy 0-100% without Barometric Relief①②
H = Economizer, Comparative Enthalpy 0-100% with Barometric Relief①②

DIGIT 15 - Supply Fan/Drive Type/Motor
0 = Standard Drive⑰
1 = Oversized Motor
2 = Optional Belt Drive Motor⑱

DIGIT 16 - Hinged Service Access & Filters
0 = Standard Panels & Standard Filters
A = Hinged Access Panels & Standard Filters
B = Standard Panels & 2" Pleated Filters
C = Hinged Access Panels & 2" Pleated Filters

DIGIT 17 - Condenser Coil Protection
0 = Standard Coil
1 = Standard Coil with Hail guard
2 = Black Epoxy Pre-Coated Condenser Coil
3 = Black Epoxy Pre-Coated Condenser Coil with Hail Guard
4 = CompleteCoat™ Condenser Coil
5 = CompleteCoat™ Condenser Coil with Hail Guard

DIGIT 18 - Through the Base Provisions Models

Note: *(Applicable to Digit 1, T or Y models)*
0 = No Through the Base Provisions
A = Through the Base Electric⑮

Note: *(Applicable to Digit 1, Y models only)*
B = Through the Base Gas Piping
C = Through the Base Electric and Gas Piping⑫

DIGIT 19 - Disconnect/Circuit Breaker/ Phase Monitor (3 phase only)
0 = No Disconnect or Circuit Breaker/No Phase Monitor⑳
1 = Unit Mounted Non-Fused Disconnect⑮
2 = Unit Mounted Circuit Breaker⑮
3 = Phase Monitor㉑
4 = Phase Monitor & Non-Fused Disconnect Switch
5 = Phase Monitor & Circuit Breaker

DIGIT 20 - Convenience Outlet
0 = No Convenience Outlet
A = Unpowered Convenience Outlet
B = Powered Convenience Outlet (3 phase only)③

DIGIT 21 - Communications Options①
0 = No Communications Interface
1 = Trane Communications Interface
2 = LonTalk® Communications Interface
3 = Novar 2024 Controls
4 = Novar 3051 Controls

DIGIT 22 - Refrigeration System Option
0 = Standard Refrigeration System④
A = Thermal Expansion Valve (TXV)
B = Dehumidification (Hot Gas Reheat Coil)⑭⑯

DIGIT 23 - Refrigeration Controls
0 = No Refrigeration Control
1 = High Pressure Control①⑥
2 = Frostat⑤
3 = Crankcase Heater⑯
4 = High Pressure Control①⑥ and Frostat⑤
5 = High Pressure Control①⑥ and Crankcase Heater⑯
6 = Frostat⑤ and Crankcase Heater⑥⑯
7 = High Pressure Control,①⑥ Frostat⑤ and Crankcase Heater⑥⑯

DIGIT 24 - Smoke Detector
0 = No Smoke Detector
A = Return Air Smoke Detector⑧⑨
B = Supply Air Smoke Detector
C = Supply and Return Air Smoke Detectors⑨

DIGIT 25 - Monitoring Controls①
0 = No Monitoring Control⑩
1 = Clogged Filter Switch⑩
2 = Fan Failure Switch⑩
3 = Discharge Air Sensing Tube⑩
4 = Clogged Filter Switch and Fan Fail Switch⑩
5 = Clogged Filter Switch and Discharge Air Sensing Tube⑩
6 = Fan Fail Switch and Discharge Air Sensing Tube⑩
7 = Clogged Filter and Fan Fail Switches and Discharge Air Sensing Tube⑩
8 = Novar Return Air Sensor⑪

Model Number Notes

① Not available with electromechanical unit controls.
② Economizer with Barometric Relief is for downflow configured units only. Order Economizer without Barometric Relief for horizontal configuration. Barometric Relief for horizontal configured units must be ordered as field installed accessory.
③ Requires use of Disconnect or Circuit Breaker.
④ Standard refrigeration metering device – short orifice.
⑤ Frostat cannot be field installed in electro-mechanical units.
⑥ High Pressure control is standard on 3-phase units with scroll compressors and in 3 ton standard efficiency units.
⑦ Not available with High Temperature Stat accessory.
⑧ The return air smoke detector may not fit up or work properly on the Precedent units when used in conjunction with 3rd party accessories such as bolt on heat wheels, economizers and power exhaust. Do not order the return air smoke detectors when using this type of accessory.
⑨ Return Air Smoke Detector cannot be ordered with Novar Controls.
⑩ These options are standard when ordering Novar Controls.
⑪ This option is used when ordering Novar Controls.
⑫ Includes gas piping and shutoff (field assembly required).
⑬ The manual outside air damper will ship factory supplied within the unit, but must be field installed.
⑭ Requires selection of 2" Pleated Filters (option B or C) for Digit 16.
⑮ Through the base electric required when ordering disconnect/ circuit breaker options.
⑯ Crankcase heaters are standard on 3 ton standard efficiency and 7.5 ton single compressor units.
⑰ Direct Drive (3-5 tons); Belt Drive (6-10 tons)
⑱ Not available on 6 ton units and all single phase or standard efficiency.
⑲ Belt drive standard on 13 SEER, R-22 products.
⑳ Phase Monitor Standard on 3-5 ton Direct Drive Indoor Motor.
㉑ Available on 3-10 ton Belt Drive Indoor Motors.

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

3 — 5 Ton
YSC036-060A

Precedent™ Convertible Pkg. Gas/Electric

Table 1 — Main Assembly — 3-5 Ton Standard Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YSC036A3*L	208-230/3/60	37,400	48,000
YSC048A3*L	208-230/3/60	49,200	48,000
YSC060A3*L	208-230/3/60	63,100	48,000
YSC036A4*L	460/3/60	37,400	48,000
YSC048A4*L	460/3/60	49,200	48,000
YSC060A4*L	460/3/60	63,100	48,000
10th Digit = Medium Heat, Standard Heat Exchanger			
YSC036A3*M	208-230/3/60	37,400	64,000
YSC048A3*M	208-230/3/60	49,200	64,000
YSC060A3*M	208-230/3/60	63,100	64,000
YSC036A4*M	460/3/60	37,400	64,000
YSC048A4*M	460/3/60	49,200	64,000
YSC060A4*M	460/3/60	63,100	64,000
10th Digit = High Heat, Standard Heat Exchanger			
YSC036A3*H	208-230/3/60	37,400	96,000
YSC048A3*H	208-230/3/60	49,200	96,000
YSC060A3*H	208-230/3/60	63,100	104,000
YSC036A4*H	460/3/60	37,400	96,000
YSC048A4*H	460/3/60	49,200	96,000
YSC060A4*H	460/3/60	63,100	104,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

6 — 10 Ton
YSC072-120A

Precedent™ Convertible Pkg. Gas/Electric

Table 1 — Main Assembly — 6-10 Ton Standard Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YSC072A3*L	208-230/3/60	72,000	64,800
YSC090A3*L	208-230/3/60	90,000	97,200
YSC092A3*L	208-230/3/60	90,000	97,200
YSC102A3*L	208-230/3/60	105,000	97,200
YSC120A3*L	208-230/3/60	117,000	121,500
YSC072A4*L	460/3/60	72,000	64,800
YSC090A4*L	460/3/60	90,000	97,200
YSC092A4*L	460/3/60	90,000	97,200
YSC102A4*L	460/3/60	105,000	97,200
YSC120A4*L	460/3/60	117,000	121,500
10th Digit = Medium Heat, Standard Heat Exchanger			
YSC072A3*M	208-230/3/60	72,000	97,200
YSC090A3*M	208-230/3/60	90,000	121,500
YSC092A3*M	208-230/3/60	90,000	121,500
YSC102A3*M	208-230/3/60	105,000	121,500
YSC120A3*M	208-230/3/60	117,000	162,000
YSC072A4*M	460/3/60	72,000	97,200
YSC090A4*M	460/3/60	90,000	121,500
YSC092A4*M	460/3/60	90,000	121,500
YSC102A4*M	460/3/60	105,000	121,500
YSC120A4*M	460/3/60	117,000	162,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

6 — 10 Ton
YSC072-120A

Precedent™ Convertible Pkg. Gas/Electric

Table 1 — Main Assembly — 6-10 Ton Standard Efficiency (Digits 1-8 & Digit 10) - Continued

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = High Heat, Standard Heat Exchanger			
YSC072A3*H	208-230/3/60	72,000	121,500
YSC090A3*H	208-230/3/60	90,000	162,000
YSC092A3*H	208-230/3/60	90,000	162,000
YSC102A3*H	208-230/3/60	105,000	162,000
YSC120A3*H	208-230/3/60	117,000	205,500
YSC072A4*H	460/3/60	72,000	121,500
YSC090A4*H	460/3/60	90,000	162,000
YSC092A4*H	460/3/60	90,000	162,000
YSC102A4*H	460/3/60	105,000	162,000
YSC120A4*H	460/3/60	117,000	205,500

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

3 — 5 Ton
YSC036-060E

Precedent™ Convertible Pkg. Gas/Electric R-410A

R-410

Table 1 — Main Assembly — 3-5 Ton Standard Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YSC036E3*L	208-230/3/60	37,150	48,000
YSC048E3*L	208-230/3/60	49,450	48,000
YSC060E3*L	208-230/3/60	62,270	48,000
YSC036E4*L	460/3/60	37,150	48,000
YSC048E4*L	460/3/60	49,450	48,000
YSC060E4*L	460/3/60	62,270	48,000
10th Digit = Medium Heat, Standard Heat Exchanger			
YSC036E3*M	208-230/3/60	37,150	64,000
YSC048E3*M	208-230/3/60	49,450	64,000
YSC060E3*M	208-230/3/60	62,270	64,000
YSC036E4*M	460/3/60	37,150	64,000
YSC048E4*M	460/3/60	49,450	64,000
YSC060E4*M	460/3/60	62,270	64,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

3 — 5 Ton
YSC036-060E

Precedent™ Convertible Pkg. Gas/Electric R-410A

R-410

Table 1 — Main Assembly — 3-5 Ton Standard Efficiency (Digits 1-8 & Digit 10) - continued

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = High Heat, Standard Heat Exchanger			
YSC036E3*H	208-230/3/60	37,150	96,000
YSC048E3*H	208-230/3/60	49,450	96,000
YSC060E3*H	208-230/3/60	62,270	104,000
YSC036E4*H	460/3/60	37,150	96,000
YSC048E4*H	460/3/60	49,450	96,000
YSC060E4*H	460/3/60	62,270	104,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

6 — 10 Ton
YSC072-120E

Precedent™ Convertible Pkg. Gas/Electric

R-410

Table 1 — Main Assembly — 6-10 Ton Standard Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YSC072E3*L	208-230/3/60	71,200	64,800
YSC092E3*L	208-230/3/60	89,300	97,200
YSC102E3*L	208-230/3/60	96,600	97,200
YSC120E3*L	208-230/3/60	110,300	121,500
YSC072E4*L	460/3/60	71,200	64,800
YSC092E4*L	460/3/60	89,300	97,200
YSC102E4*L	460/3/60	96,600	97,200
YSC120E4*L	460/3/60	110,300	121,500
10th Digit = Medium Heat, Standard Heat Exchanger			
YSC072E3*M	208-230/3/60	71,200	97,200
YSC092E3*M	208-230/3/60	89,300	121,500
YSC102E3*M	208-230/3/60	96,600	121,500
YSC120E3*M	208-230/3/60	110,300	162,000
YSC072E4*M	460/3/60	71,200	97,200
YSC092E4*M	460/3/60	89,300	121,500
YSC102E4*M	460/3/60	96,600	121,500
YSC120E4*M	460/3/60	110,300	162,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

6 — 10 Ton
YSC072-120E

Precedent™ Convertible Pkg. Gas/Electric

R-410

Table 1 — Main Assembly — 6-10 Ton Standard Efficiency (Digits 1-8 & Digit 10) - Continued

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = High Heat, Standard Heat Exchanger			
YSC072E3*H	208-230/3/60	71,200	121,500
YSC092E3*H	208-230/3/60	89,300	162,000
YSC102E3*H	208-230/3/60	96,600	162,000
YSC120E3*H	208-230/3/60	110,300	205,500
YSC072E4*H	460/3/60	71,200	121,500
YSC092E4*H	460/3/60	89,300	162,000
YSC102E4*H	460/3/60	96,600	162,000
YSC120E4*H	460/3/60	110,300	205,500

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

3 — 5 Ton
YHC033-063A

Precedent™ Convertible Pkg. Gas/Electric

Table 1 — Main Assembly — 13 SEER High Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YHC033A3*L	208-230/3/60	38,000	48,000
YHC043A3*L	208-230/3/60	49,800	48,000
YHC063A3*L	208-230/3/60	62,400	48,000
YHC033A4*L	460/3/60	38,000	48,000
YHC043A4*L	460/3/60	49,800	48,000
YHC063A4*L	460/3/60	62,400	48,000
10th Digit = Medium Heat, Standard Heat Exchanger			
YHC033A3*M	208-230/3/60	38,000	64,000
YHC043A3*M	208-230/3/60	49,800	64,000
YHC063A3*M	208-230/3/60	62,400	64,000
YHC033A4*M	460/3/60	38,000	64,000
YHC043A4*M	460/3/60	49,800	64,000
YHC063A4*M	460/3/60	62,400	64,000
10th Digit = High Heat, Standard Heat Exchanger			
YHC033A3*H	208-230/3/60	38,000	96,000
YHC043A3*H	208-230/3/60	49,800	96,000
YHC063A3*H	208-230/3/60	62,400	104,000
YHC033A4*H	460/3/60	38,000	96,000
YHC043A4*H	460/3/60	49,800	96,000
YHC063A4*H	460/3/60	62,400	104,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

6 — 10 Ton
YHC072-120A

Precedent™ Convertible Pkg. Gas/Electric

Table 2 — Main Assembly — 6-10 Ton High Efficiency (Digits 1-8 & Digit 10) - Continued

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
10th Digit = Low Heat, Standard Heat Exchanger			
YHC072A3*L	208-230/3/60	72,000	64,800
YHC092A3*L	208-230/3/60	90,000	97,200
YHC102A3*L	208-230/3/60	102,000	97,200
YHC120A3*L	208-230/3/60	116,000	121,500
YHC072A4*L	460/3/60	72,000	64,800
YHC092A4*L	460/3/60	90,000	97,200
YHC102A4*L	460/3/60	102,000	97,200
YHC120A4*L	460/3/60	116,000	121,500
10th Digit = Medium Heat, Standard Heat Exchanger			
YHC072A3*M	208-230/3/60	72,000	97,200
YHC092A3*M	208-230/3/60	90,000	121,500
YHC102A3*M	208-230/3/60	102,000	121,500
YHC120A3*M	208-230/3/60	116,000	162,000
YHC072A4*M	460/3/60	72,000	97,200
YHC092A4*M	460/3/60	90,000	121,500
YHC102A4*M	460/3/60	102,000	121,500
YHC120A4*M	460/3/60	116,000	162,000
10th Digit = High Heat, Standard Heat Exchanger			
YHC072A3*H	208-230/3/60	72,000	121,500
YHC092A3*H	208-230/3/60	90,000	162,000
YHC102A3*H	208-230/3/60	102,000	162,000
YHC120A3*H	208-230/3/60	116,000	202,500
YHC072A4*H	460/3/60	72,000	121,500
YHC092A4*H	460/3/60	90,000	162,000
YHC102A4*H	460/3/60	102,000	162,000
YHC120A4*H	460/3/60	116,000	202,500

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

3 — 5 Ton
YHC036-060E

Precedent™ Convertible Pkg. Gas/Electric

R-410

Table 2 — Main Assembly — 3-5 High Efficiency (Digits 1-8 & Digit 10)

Model Number	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YHC036E3*L	208-230/3/60	38,000	48,000
YHC048E3*L	208-230/3/60	48,000	48,000
YHC060E3*L	208-230/3/60	58,000	48,000
YHC036E4*L	460/3/60	38,000	48,000
YHC048E4*L	460/3/60	48,000	48,000
YHC060E4*L	460/3/60	58,000	48,000
10th Digit = Medium Heat, Standard Heat Exchanger			
YHC036E3*M	208-230/3/60	38,000	64,000
YHC048E3*M	208-230/3/60	48,000	64,000
YHC060E3*M	208-230/3/60	58,000	64,000
YHC036E4*M	460/3/60	38,000	64,000
YHC048E4*M	460/3/60	48,000	64,000
YHC060E4*M	460/3/60	58,000	64,000
10th Digit = High Heat, Standard Heat Exchanger			
YHC036E3*H	208-230/3/60	38,000	96,000
YHC048E3*H	208-230/3/60	48,000	96,000
YHC060E3*H	208-230/3/60	58,000	104,000
YHC036E4*H	460/3/60	38,000	96,000
YHC048E4*H	460/3/60	48,000	96,000
YHC060E4*H	460/3/60	58,000	104,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

Model Nomenclature Voyager R-22

Y	C	D	150	C	0	0	A	A
1	2	3	456	7	9	10	11	12

DIGIT 1,2 — Unit Type
TC = Packaged Cooling, Electric Heat
TF = With Factory Installed Options
YC = Packaged Gas/Electric
YF = With Factory Installed Options

DIGIT 3 — Airflow Configuration
D = Downflow
H = Horizontal

DIGIT 4,5,6 — Nominal Gross Cooling Capacity (MBh)
150 = 12½ Tons Standard Efficiency
151 = 12½ Tons High Efficiency
180 = 15 Tons Standard Efficiency
181 = 15 Tons High Efficiency
210 = 17½ Tons Standard Efficiency
211 = 17½ Tons High Efficiency
240 = 20 Tons Standard Efficiency
241 = 20 Tons High Efficiency
300 = 25 Tons Standard Efficiency
301 = 25 Tons High Efficiency

DIGIT 7 — Major Design Sequence

DIGIT 8 — Voltage Selection
3 = 208-230/3/60
4 = 460/3/60
W = 575/3/60
K = 380/3/60

DIGIT 9,10 — Factory Installed Options

Note: *(Applicable to Digit 1, 2 T models only)*
00 = No Factory-Installed Options
0A = Factory-Installed Economizer
0B = Oversized Motor
0C = Downflow Economizer and Oversized Motor
0F = Trane Communications Interface (TCI)
0G = Downflow Economizer and TCI
0H = TXV/Face-Split Evaporator
0J = Oversized Motor and TXV Face-Split Evaporator
0K = Downflow Economizer, Oversized Motor, and TXV Face-Split Evaporator
0L = Downflow Economizer with TXV/Face-Split Evaporator
0M = Reheat Coil
0N = Downflow Economizer and Reheat Coil
0P = Oversized Motor and Reheat Coil
0R = Downflow Economizer, Oversized Motor and Reheat Coil

DIGIT 9 — Heating Capacity

Note: *(Applicable to Digit 1, 2 Y models only)*
L = Low Heat
H = High Heat
V = Modulating Gas Heat

DIGIT 10 — Factory Installed Options⑥

Note: *(Applicable to Digit 1, 2 Y models only)*
0 = Packed Stock, No Options
A = Downflow Economizer①
B = Oversized Motor⑧
C = Downflow Economizer and Oversized Motor①
F = Trane Communications Interface (TCI)⑧⑰
G = Downflow Economizer & TCI①⑰
H = TXV/Face-Split Evaporator⑭
J = Oversized Motor and TXV/Face Split Evaporator⑭
K = Downflow Economizer, Oversized Motor, and TXV/Face Split Evaporator①⑭
L = Downflow Economizer with TXV Face-Split Evaporator⑧⑭
M = Reheat Coil④⑭
N = Downflow Economizer and Reheat Coil①④⑭
P = Oversized Motor and Reheat Coil①④⑭
R = Downflow Economizer, Oversized Motor and Reheat Coil①④⑭

DIGIT 11 — Minor Design Sequence

DIGIT 12 — Service Sequence

Note: Explanation of Model Number Notes located on this page.

Note: Most Factory Installed Options (FIOPS) available for Downflow Air Discharge units only. Please verify with ordering system for availability.

Options

Factory Installed Options⑮
- 2" Pleated Filters③②
- Black Epoxy Pre-Coated Coils⑧
- Dehumidification Option②⑪⑭
- Differential Pressure Switches
- High Efficiency Motors⑥
- Hinged Access Doors
- Novar Return Air Sensor⑱
- Novar Unit Controls⑯
- Powered or Unpowered Convenience Outlet⑤
- Stainless Steel Heat Exchanger with 10-year warranty⑤
- Supply and/or Return Air Smoke Detector②⑩
- Thermal Expansion Valve⑭
- Through the Base Electrical Access
- Through the Base Electrical with Circuit Breaker⑪⑫
- Through the Base Electrical with Disconnect Switch⑦⑪⑫

Factory* or Field Installed Options⑮
- Barometric Relief
- Clogged Filter/Fan Failure Switch②⑥
- Discharge Air Sensing Kit②⑥
- Economizer (Downflow)①
- Electric Heaters⑥⑧⑫
- Frostat②④⑥
- LonTalk® Communications Interface (LCI)⑥
- Oversized Motors⑥
- Reference or Comparative③⑥ Enthalpy
- Tool-less Hail Guards⑥
- Trane Communications Interface (TCI)⑥⑰

Field Installed Options
- CO_2 Sensing
- Digital Display Zone Sensor
- Dual Thermistor Remote Zone Sensor
- Economizer (Horizontal)
- High Altitude Kit
- High and Low Static Drive Kits
- Humidity Sensor
- Low Static Drive
- LP Conversion Kit
- Manual Outside Air Damper
- Motorized Outside Air Dampers
- Powered Exhaust
- Quick Start Kit
- ReliaTel™ Options Module⑨
- Remote Potentiometer
- Roof Curb (Downflow Only)
- Thermostat
- Ventilation Override Accessory②
- Zone Sensors and Remote Zone Sensors

Model Number Notes

① Some field set up required.

② Requires ReliaTel options module.

③ Requires Economizer.

④ All 10th digit model numbers including reheat coil (M,N,P,R) require additional factory installed options; ReliaTel™options module, Frostat, and 2" pleated filters.

⑤ Must be ordered with Through-the-Base Electrical option or Horizontal-Side Access and either Unit Mounted Disconnect or Circuit Breaker.

⑥ Available factory installed on downflow AND horizontal units. Verify with ordering system.

⑦ Cannot be fused.

⑧ Must be factory installed when using Through-the-Base Options.

⑨ ReliaTel™ Options Module is required when ordering the following accessories: Clogged Filter Switch, Fan Fail Switch, Discharge Air Sensing Kit, Frostat, Ventilation Override, Smoke Detector, Dehumidification and Modulating Gas Heat Furnace.

⑩ Option cannot be ordered in conjunction with field installed economizer on downflow units. Must be factory installed. The return air smoke detector may not fit up or work properly on the Voyager units when used in conjunction with 3rd party accessories (such as bolt on heat wheels, economizers, and power exhaust). Do not order the return air smoke detectors when using this type of accessory.

⑪ Unit mounted disconnect and circuit breakers are mutually exclusive of each other.

⑫ Through-the-base electrical option or Horizontal-Side Access must be ordered with either unit mounted disconnect or circuit breaker. When adding heat, must order Trane Electric Heat.

⑬ This option consists of the Novar return air sensor (Novar #WTS-10) that is wired and shipped in the return air section of the unit. The sensor ships with approximately 15' of extra wire for dropping down the return air duct (downflow only).

⑭ Available on high efficiency, downflow units only.

⑮ All Factory Installed Options are Built-to-Order. Check order services for estimated production cycle.

⑯ The Novar control option includes the following factory installed and wired devices: Novar ETM-2024 or Novar 3051 rooftop controller, fan proving switch, clogged filter or unit shutdown switch, Cool 1, Cool 2, Heat switch and discharge air sensor (Novar 2024 is downflow only). Note:Option cannot be ordered in conjunction with FIOPS Smoke Detector option.

⑰ TCI is for use with non-VariTrac systems and VariTrac systems.

Note: **Most Factory Installed Options (FIOPS) available for Downflow Air Discharge units only. Please verify with ordering system for availability.*

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

12-1/2 Ton YCH150D

Horizontal Packaged Gas/Electric

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH150D3L0B	—	208-230/3/60	150,000	122,000
YCH150D3LBB	Ov Motor	208-230/3/60	150,000	122,000
YCH150D3LFB	TCI	208-230/3/60	150,000	122,000
YCH150D3H0B	—	208-230/3/60	150,000	203,000
YCH150D3HBB	Ov Motor	208-230/3/60	150,000	203,000
YCH150D3HFB	TCI	208-230/3/60	150,000	203,000
YCH150D4L0B	—	460/3/60	150,000	122,000
YCH150D4LBB	Ov Motor	460/3/60	150,000	122,000
YCH150D4LFB	TCI	460/3/60	150,000	122,000
YCH150D4H0B	—	460/3/60	150,000	203,000
YCH150D4HBB	Ov Motor	460/3/60	150,000	203,000
YCH150D4HFB	TCI	460/3/60	150,000	203,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Short orifice refrigerant control
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Sloped sheet metal drain pan
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**
- **Optional extended warranties**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

12-1/2 Ton YCD150D

Downflow Packaged Gas/Electric

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD150D3L0B	—	208-230/3/60	150,000	122,000
YCD150D3LAB	Economizer	208-230/3/60	150,000	122,000
YCD150D3LBB	Ov Motor	208-230/3/60	150,000	122,000
YCD150D3LCB	Econ/OvMtr	208-230/3/60	150,000	122,000
YCD150D3LFB	TCI	208-230/3/60	150,000	122,000
YCD150D3LGB	Econ/TCI	208-230/3/60	150,000	122,000
YCD150D3H0B	—	208-230/3/60	150,000	203,000
YCD150D3HAB	Economizer	208-230/3/60	150,000	203,000
YCD150D3HBB	Ov Motor	208-230/3/60	150,000	203,000
YCD150D3HCB	Econ/OvMtr	208-230/3/60	150,000	203,000
YCD150D3HFB	TCI	208-230/3/60	150,000	203,000
YCD150D3HGB	Econ/TCI	208-230/3/60	150,000	203,000
YCD150D4L0B	—	460/3/60	150,000	122,000
YCD150D4LAB	Economizer	460/3/60	150,000	122,000
YCD150D4LBB	Ov Motor	460/3/60	150,000	122,000
YCD150D4LCB	Econ/OvMtr	460/3/60	150,000	122,000
YCD150D4LFB	TCI	460/3/60	150,000	122,000
YCD150D4LGB	Econ/TCI	460/3/60	150,000	122,000
YCD150D4H0B	—	460/3/60	150,000	203,000
YCD150D4HAB	Economizer	460/3/60	150,000	203,000
YCD150D4HBB	Ov Motor	460/3/60	150,000	203,000
YCD150D4HCB	Econ/OvMtr	460/3/60	150,000	203,000
YCD150D4HFB	TCI	460/3/60	150,000	203,000
YCD150D4HGB	Econ/TCI	460/3/60	150,000	203,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

15 Ton YCH180B

Horizontal Packaged Gas/Electric

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH180B3L0H	—	208-230/3/60	182,000	203,000
YCH180B3LBH	Ov Motor	208-230/3/60	182,000	203,000
YCH180B3LFH	TCI	208-230/3/60	182,000	203,000
YCH180B3H0H	—	208-230/3/60	182,000	284,000
YCH180B3HBH	Ov Motor	208-230/3/60	182,000	284,000
YCH180B3HFH	TCI	208-230/3/60	182,000	284,000
YCH180B4L0H	—	460/3/60	182,000	203,000
YCH180B4LBH	Ov Motor	460/3/60	182,000	203,000
YCH180B4LFH	TCI	460/3/60	182,000	203,000
YCH180B4H0H	—	460/3/60	182,000	284,000
YCH180B4HBH	Ov Motor	460/3/60	182,000	284,000
YCH180B4HFH	TCI	460/3/60	182,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Short orifice refrigerant control
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Sloped sheet metal drain pan
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**
- **Optional extended warranties**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

15 Ton
YCD180B

Downflow Packaged Gas/Electric

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD180B3L0H	—	208-230/3/60	182,000	203,000
YCD180B3LAH	Economizer	208-230/3/60	182,000	203,000
YCD180B3LBH	Ov Motor	208-230/3/60	182,000	203,000
YCD180B3LCH	Econ/OvMtr	208-230/3/60	182,000	203,000
YCD180B3LFH	TCI	208-230/3/60	182,000	203,000
YCD180B3LGH	Econ/TCI	208-230/3/60	182,000	203,000
YCD180B3H0H	—	208-230/3/60	182,000	284,000
YCD180B3HAH	Economizer	208-230/3/60	182,000	284,000
YCD180B3HBH	Ov Motor	208-230/3/60	182,000	284,000
YCD180B3HCH	Econ/OvMtr	208-230/3/60	182,000	284,000
YCD180B3HFH	TCI	208-230/3/60	182,000	284,000
YCD180B3HGH	Econ/TCI	208-230/3/60	182,000	284,000
YCD180B4L0H	—	460/3/60	182,000	203,000
YCD180B4LAH	Economizer	460/3/60	182,000	203,000
YCD180B4LBH	Ov Motor	460/3/60	182,000	203,000
YCD180B4LCH	Econ/OvMtr	460/3/60	182,000	203,000
YCD180B4LFH	TCI	460/3/60	182,000	203,000
YCD180B4LGH	Econ/TCI	460/3/60	182,000	203,000
YCD180B4H0H	—	460/3/60	182,000	284,000
YCD180B4HAH	Economizer	460/3/60	182,000	284,000
YCD180B4HBH	Ov Motor	460/3/60	182,000	284,000
YCD180B4HCH	Econ/OvMtr	460/3/60	182,000	284,000
YCD180B4HFH	TCI	460/3/60	182,000	284,000
YCD180B4HGH	Econ/TCI	460/3/60	182,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Sloped sheet metal drain pan
- Internally enhanced coil tubing
- Low ambient cooling to 0°F standard
- colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

17-1/2Ton YCH210C

Horizontal Packaged Gas/Electric

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH210C3L0E	—	208-230/3/60	210,000	203,000
YCH210C3LBE	Ov Motor	208-230/3/60	210,000	203,000
YCH210C3LFE	TCI	208-230/3/60	210,000	203,000
YCH210C3H0E	—	208-230/3/60	210,000	284,000
YCH210C3HBE	Ov Motor	208-230/3/60	210,000	284,000
YCH210C3HFE	TCI	208-230/3/60	210,000	284,000
YCH210C4L0E	—	460/3/60	210,000	203,000
YCH210C4LBE	Ov Motor	460/3/60	210,000	203,000
YCH210C4LFE	TCI	460/3/60	210,000	203,000
YCH210C4H0E	—	460/3/60	210,000	284,000
YCH210C4HBE	Ov Motor	460/3/60	210,000	284,000
YCH210C4HFE	TCI	460/3/60	210,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Short orifice refrigerant control
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Sloped sheet metal drain pan
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty on 17-1/2 ton units**
- **Optional extended warranties**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

17-1/2Ton YCD210C

Downflow Packaged Gas/Electric

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD210C3L0E	—	208-230/3/60	210,000	203,000
YCD210C3LAE	Economizer	208-230/3/60	210,000	203,000
YCD210C3LBE	Ov Motor	208-230/3/60	210,000	203,000
YCD210C3LCE	Econ/OvMtr	208-230/3/60	210,000	203,000
YCD210C3LFE	TCI	208-230/3/60	210,000	203,000
YCD210C3LGE	Econ/TCI	208-230/3/60	210,000	203,000
YCD210C3H0E	—	208-230/3/60	210,000	284,000
YCD210C3HAE	Economizer	208-230/3/60	210,000	284,000
YCD210C3HBE	Ov Motor	208-230/3/60	210,000	284,000
YCD210C3HCE	Econ/OvMtr	208-230/3/60	210,000	284,000
YCD210C3HFE	TCI	208-230/3/60	210,000	284,000
YCD210C3HGE	Econ/TCI	208-230/3/60	210,000	284,000
YCD210C4L0E	—	460/3/60	210,000	203,000
YCD210C4LAE	Economizer	460/3/60	210,000	203,000
YCD210C4LBE	Ov Motor	460/3/60	210,000	203,000
YCD210C4LCE	Econ/OvMtr	460/3/60	210,000	203,000
YCD210C4LFE	TCI	460/3/60	210,000	203,000
YCD210C4LGE	Econ/TCI	460/3/60	210,000	203,000
YCD210C4H0E	—	460/3/60	210,000	284,000
YCD210C4HAE	Economizer	460/3/60	210,000	284,000
YCD210C4HBE	Ov Motor	460/3/60	210,000	284,000
YCD210C4HCE	Econ/OvMtr	460/3/60	210,000	284,000
YCD210C4HFE	TCI	460/3/60	210,000	284,000
YCD210C4HGE	Econ/TCI	460/3/60	210,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Sloped sheet metal drain pan
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

20 Ton YCH240B

Horizontal Packaged Gas/Electric

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH240B3L0J	—	208-230/3/60	242,000	203,000
YCH240B3LBJ	Ov Motor	208-230/3/60	242,000	203,000
YCH240B3LFJ	TCI	208-230/3/60	242,000	203,000
YCH240B3H0J	—	208-230/3/60	242,000	324,000
YCH240B3HBJ	Ov Motor	208-230/3/60	242,000	324,000
YCH240B3HFJ	TCI	208-230/3/60	242,000	324,000
YCH240B4L0J	—	460/3/60	242,000	203,000
YCH240B4LBJ	Ov Motor	460/3/60	242,000	203,000
YCH240B4LFJ	TCI	460/3/60	242,000	203,000
YCH240B4H0J	—	460/3/60	242,000	324,000
YCH240B4HBJ	Ov Motor	460/3/60	242,000	324,000
YCH240B4HFJ	TCI	460/3/60	242,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Short orifice refrigerant control
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Sloped sheet metal drain pan
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**
- **Optional extended warranties**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

20 Ton YCD240B

Downflow Packaged Gas/Electric

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD240B3L0J	—	208-230/3/60	242,000	203,000
YCD240B3LAJ	Economizer	208-230/3/60	242,000	203,000
YCD240B3LBJ	Ov Motor	208-230/3/60	242,000	203,000
YCD240B3LCJ	Econ/OvMtr	208-230/3/60	242,000	203,000
YCD240B3LFJ	TCI	208-230/3/60	242,000	203,000
YCD240B3LGJ	Econ/TCI	208-230/3/60	242,000	203,000
YCD240B3H0J	—	208-230/3/60	242,000	324,000
YCD240B3HAJ	Economizer	208-230/3/60	242,000	324,000
YCD240B3HBJ	Ov Motor	208-230/3/60	242,000	324,000
YCD240B3HCJ	Econ/OvMtr	208-230/3/60	242,000	324,000
YCD240B3HFJ	TCI	208-230/3/60	242,000	324,000
YCD240B3HGJ	Econ/TCI	208-230/3/60	242,000	324,000
YCD240B4L0J	—	460/3/60	242,000	203,000
YCD240B4LAJ	Economizer	460/3/60	242,000	203,000
YCD240B4LBJ	Ov Motor	460/3/60	242,000	203,000
YCD240B4LCJ	Econ/OvMtr	460/3/60	242,000	203,000
YCD240B4LFJ	TCI	460/3/60	242,000	203,000
YCD240B4LGJ	Econ/TCI	460/3/60	242,000	203,000
YCD240B4H0J	—	460/3/60	242,000	324,000
YCD240B4HAJ	Economizer	460/3/60	242,000	324,000
YCD240B4HBJ	Ov Motor	460/3/60	242,000	324,000
YCD240B4HCJ	Econ/OvMtr	460/3/60	242,000	324,000
YCD240B4HFJ	TCI	460/3/60	242,000	324,000
YCD240B4HGJ	Econ/TCI	460/3/60	242,000	324,000

Features:

- **RellaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

25 Ton
YCH300B

Horizontal Packaged Gas/Electric

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH300B3L0H	—	208-230/3/60	290,000	203,000
YCH300B3LFH	TCI	208-230/3/60	290,000	203,000
YCH300B3H0H	—	208-230/3/60	290,000	324,000
YCH300B3HFH	TCI	208-230/3/60	290,000	324,000
YCH300B4L0H	—	460/3/60	290,000	203,000
YCH300B4LFH	TCI	460/3/60	290,000	203,000
YCH300B4H0H	—	460/3/60	290,000	324,000
YCH300B4HFH	TCI	460/3/60	290,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

25 Ton YCD300B

Downflow Packaged Gas/Electric

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD300B3L0H	—	208-230/3/60	246,000	203,000
YCD300B3LAH	Economizer	208-230/3/60	246,000	203,000
YCD300B3LFH	TCI	208-230/3/60	246,000	203,000
YCD300B3LGH	Econ/TCI	208-230/3/60	246,000	203,000
YCD300B3H0H	—	208-230/3/60	246,000	324,000
YCD300B3HAH	Economizer	208-230/3/60	246,000	324,000
YCD300B3HFH	TCI	208-230/3/60	246,000	324,000
YCD300B3HGH	Econ/TCI	208-230/3/60	246,000	324,000
YCD300B4L0H	—	460/3/60	246,000	203,000
YCD300B4LAH	Economizer	460/3/60	246,000	203,000
YCD300B4LFH	TCI	460/3/60	246,000	203,000
YCD300B4LGH	Econ/TCI	460/3/60	246,000	203,000
YCD300B4H0H	—	460/3/60	246,000	324,000
YCD300B4HAH	Economizer	460/3/60	246,000	324,000
YCD300B4HFH	TCI	460/3/60	246,000	324,000
YCD300B4HGH	Econ/TCI	460/3/60	246,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

12-1/2 Ton
YCD150E

Downflow Packaged Gas/Electric

R-410

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD150E3L0A	—	208-230/3/60	148,000	122,000
YCD150E3LAA	Economizer	208-230/3/60	148,000	122,000
YCD150E3LBA	Ov Motor	208-230/3/60	148,000	122,000
YCD150E3LCA	Econ/OvMtr	208-230/3/60	148,000	122,000
YCD150E3LFA	TCI	208-230/3/60	148,000	122,000
YCD150E3LGA	Econ/TCI	208-230/3/60	148,000	122,000
YCD150E3H0A	—	208-230/3/60	148,000	203,000
YCD150E3HAA	Economizer	208-230/3/60	148,000	203,000
YCD150E3HBA	Ov Motor	208-230/3/60	148,000	203,000
YCD150E3HCA	Econ/OvMtr	208-230/3/60	148,000	203,000
YCD150E3HFA	TCI	208-230/3/60	148,000	203,000
YCD150E3HGA	Econ/TCI	208-230/3/60	148,000	203,000
YCD150E4L0A	—	460/3/60	148,000	122,000
YCD150E4LAA	Economizer	460/3/60	148,000	122,000
YCD150E4LBA	Ov Motor	460/3/60	148,000	122,000
YCD150E4LCA	Econ/OvMtr	460/3/60	148,000	122,000
YCD150E4LFA	TCI	460/3/60	148,000	122,000
YCD150E4LGA	Econ/TCI	460/3/60	148,000	122,000
YCD150E4H0A	—	460/3/60	148,000	203,000
YCD150E4HAA	Economizer	460/3/60	148,000	203,000
YCD150E4HBA	Ov Motor	460/3/60	148,000	203,000
YCD150E4HCA	Econ/OvMtr	460/3/60	148,000	203,000
YCD150E4HFA	TCI	460/3/60	148,000	203,000
YCD150E4HGA	Econ/TCI	460/3/60	148,000	203,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

12-1/2 Ton YCH150E

Horizontal Packaged Gas/Electric

R-410

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH150E3L0A	—	208-230/3/60	148,000	122,000
YCH150E3LBA	Ov Motor	208-230/3/60	148,000	122,000
YCH150E3LFA	TCI	208-230/3/60	148,000	122,000
YCH150E3H0A	—	208-230/3/60	148,000	203,000
YCH150E3HBA	Ov Motor	208-230/3/60	148,000	203,000
YCH150E3HFA	TCI	208-230/3/60	148,000	203,000
YCH150E4L0A	—	460/3/60	148,000	122,000
YCH150E4LBA	Ov Motor	460/3/60	148,000	122,000
YCH150E4LFA	TCI	460/3/60	148,000	122,000
YCH150E4H0A	—	460/3/60	148,000	203,000
YCH150E4HBA	Ov Motor	460/3/60	148,000	203,000
YCH150E4HFA	TCI	460/3/60	148,000	203,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-410A
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Short orifice refrigerant control
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Sloped sheet metal drain pan
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

15 Ton
YCD180E

Downflow Packaged Gas/Electric R-410

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD180E3L0A	—	208-230/3/60	178,000	203,000
YCD180E3LAA	Economizer	208-230/3/60	178,000	203,000
YCD180E3LBA	Ov Motor	208-230/3/60	178,000	203,000
YCD180E3LCA	Econ/OvMtr	208-230/3/60	178,000	203,000
YCD180E3LFA	TCI	208-230/3/60	178,000	203,000
YCD180E3LGA	Econ/TCI	208-230/3/60	178,000	203,000
YCD180E3H0A	—	208-230/3/60	178,000	284,000
YCD180E3HAA	Economizer	208-230/3/60	178,000	284,000
YCD180E3HBA	Ov Motor	208-230/3/60	178,000	284,000
YCD180E3HCA	Econ/OvMtr	208-230/3/60	178,000	284,000
YCD180E3HFA	TCI	208-230/3/60	178,000	284,000
YCD180E3HGA	Econ/TCI	208-230/3/60	178,000	284,000
YCD180E4L0A	—	460/3/60	178,000	203,000
YCD180E4LAA	Economizer	460/3/60	178,000	203,000
YCD180E4LBA	Ov Motor	460/3/60	178,000	203,000
YCD180E4LCA	Econ/OvMtr	460/3/60	178,000	203,000
YCD180E4LFA	TCI	460/3/60	178,000	203,000
YCD180E4LGA	Econ/TCI	460/3/60	178,000	203,000
YCD180E4H0A	—	460/3/60	178,000	284,000
YCD180E4HAA	Economizer	460/3/60	178,000	284,000
YCD180E4HBA	Ov Motor	460/3/60	178,000	284,000
YCD180E4HCA	Econ/OvMtr	460/3/60	178,000	284,000
YCD180E4HFA	TCI	460/3/60	178,000	284,000
YCD180E4HGA	Econ/TCI	460/3/60	178,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-410A
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Sloped sheet metal drain pan
- Internally enhanced coil tubing
- Low ambient cooling to 0°F standard
- colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

15 Ton
YCH180E

Horizontal Packaged Gas/Electric

R-410

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH180E3L0A	—	208-230/3/60	178,000	203,000
YCH180E3LBA	Ov Motor	208-230/3/60	178,000	203,000
YCH180E3LFA	TCI	208-230/3/60	178,000	203,000
YCH180E3H0A	—	208-230/3/60	178,000	284,000
YCH180E3HBA	Ov Motor	208-230/3/60	178,000	284,000
YCH180E3HFA	TCI	208-230/3/60	178,000	284,000
YCH180E4L0A	—	460/3/60	178,000	203,000
YCH180E4LBA	Ov Motor	460/3/60	178,000	203,000
YCH180E4LFA	TCI	460/3/60	178,000	203,000
YCH180E4H0A	—	460/3/60	178,000	284,000
YCH180E4HBA	Ov Motor	460/3/60	178,000	284,000
YCH180E4HFA	TCI	460/3/60	178,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-410A
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Short orifice refrigerant control
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Sloped sheet metal drain pan
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

17-1/2Ton YCD210E

Downflow Packaged Gas/Electric

R-410

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD210E3L0A	—	208-230/3/60	198,000	203,000
YCD210E3LAA	Economizer	208-230/3/60	198,000	203,000
YCD210E3LBA	Ov Motor	208-230/3/60	198,000	203,000
YCD210E3LCA	Econ/OvMtr	208-230/3/60	198,000	203,000
YCD210E3LFA	TCI	208-230/3/60	198,000	203,000
YCD210E3LGA	Econ/TCI	208-230/3/60	198,000	203,000
YCD210E3H0A	—	208-230/3/60	198,000	284,000
YCD210E3HAA	Economizer	208-230/3/60	198,000	284,000
YCD210E3HBA	Ov Motor	208-230/3/60	198,000	284,000
YCD210E3HCA	Econ/OvMtr	208-230/3/60	198,000	284,000
YCD210E3HFA	TCI	208-230/3/60	198,000	284,000
YCD210E3HGA	Econ/TCI	208-230/3/60	198,000	284,000
YCD210E4L0A	—	460/3/60	198,000	203,000
YCD210E4LAA	Economizer	460/3/60	198,000	203,000
YCD210E4LBA	Ov Motor	460/3/60	198,000	203,000
YCD210E4LCA	Econ/OvMtr	460/3/60	198,000	203,000
YCD210E4LFA	TCI	460/3/60	198,000	203,000
YCD210E4LGA	Econ/TCI	460/3/60	198,000	203,000
YCD210E4H0A	—	460/3/60	198,000	284,000
YCD210E4HAA	Economizer	460/3/60	198,000	284,000
YCD210E4HBA	Ov Motor	460/3/60	198,000	284,000
YCD210E4HCA	Econ/OvMtr	460/3/60	198,000	284,000
YCD210E4HFA	TCI	460/3/60	198,000	284,000
YCD210E4HGA	Econ/TCI	460/3/60	198,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-410A
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Sloped sheet metal drain pan
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

17-1/2Ton YCH210E

Horizontal Packaged Gas/Electric

R-410

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH210E3L0A	—	208-230/3/60	198,000	203,000
YCH210E3LBA	Ov Motor	208-230/3/60	198,000	203,000
YCH210E3LFA	TCI	208-230/3/60	198,000	203,000
YCH210E3H0A	—	208-230/3/60	198,000	284,000
YCH210E3HBA	Ov Motor	208-230/3/60	198,000	284,000
YCH210E3HFA	TCI	208-230/3/60	198,000	284,000
YCH210E4L0A	—	460/3/60	198,000	203,000
YCH210E4LBA	Ov Motor	460/3/60	198,000	203,000
YCH210E4LFA	TCI	460/3/60	198,000	203,000
YCH210E4H0A	—	460/3/60	198,000	284,000
YCH210E4HBA	Ov Motor	460/3/60	198,000	284,000
YCH210E4HFA	TCI	460/3/60	198,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-410A
- Short orifice refrigerant control
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Sloped sheet metal drain pan
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty on 17-1/2 ton units**
- **Optional extended warranties**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

20 Ton YCD240E

Downflow Packaged Gas/Electric

R-410

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD240E3L0A	—	208-230/3/60	240,000	203,000
YCD240E3LAA	Economizer	208-230/3/60	240,000	203,000
YCD240E3LBA	Ov Motor	208-230/3/60	240,000	203,000
YCD240E3LCA	Econ/OvMtr	208-230/3/60	240,000	203,000
YCD240E3LFA	TCI	208-230/3/60	240,000	203,000
YCD240E3LGA	Econ/TCI	208-230/3/60	240,000	203,000
YCD240E3H0A	—	208-230/3/60	240,000	324,000
YCD240E3HAA	Economizer	208-230/3/60	240,000	324,000
YCD240E3HBA	Ov Motor	208-230/3/60	240,000	324,000
YCD240E3HCA	Econ/OvMtr	208-230/3/60	240,000	324,000
YCD240E3HFA	TCI	208-230/3/60	240,000	324,000
YCD240E3HGA	Econ/TCI	208-230/3/60	240,000	324,000
YCD240E4L0A	—	460/3/60	240,000	203,000
YCD240E4LAA	Economizer	460/3/60	240,000	203,000
YCD240E4LBA	Ov Motor	460/3/60	240,000	203,000
YCD240E4LCA	Econ/OvMtr	460/3/60	240,000	203,000
YCD240E4LFA	TCI	460/3/60	240,000	203,000
YCD240E4LGA	Econ/TCI	460/3/60	240,000	203,000
YCD240E4H0A	—	460/3/60	240,000	324,000
YCD240E4HAA	Economizer	460/3/60	240,000	324,000
YCD240E4HBA	Ov Motor	460/3/60	240,000	324,000
YCD240E4HCA	Econ/OvMtr	460/3/60	240,000	324,000
YCD240E4HFA	TCI	460/3/60	240,000	324,000
YCD240E4HGA	Econ/TCI	460/3/60	240,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-410A
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

20 Ton YCH240E

Horizontal Packaged Gas/Electric

R-410

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH240E3L0A	—	208-230/3/60	240,000	203,000
YCH240E3LBA	Ov Motor	208-230/3/60	240,000	203,000
YCH240E3LFA	TCI	208-230/3/60	240,000	203,000
YCH240E3H0A	—	208-230/3/60	240,000	324,000
YCH240E3HBA	Ov Motor	208-230/3/60	240,000	324,000
YCH240E3HFA	TCI	208-230/3/60	240,000	324,000
YCH240E4L0A	—	460/3/60	240,000	203,000
YCH240E4LBA	Ov Motor	460/3/60	240,000	203,000
YCH240E4LFA	TCI	460/3/60	240,000	203,000
YCH240E4H0A	—	460/3/60	240,000	324,000
YCH240E4HBA	Ov Motor	460/3/60	240,000	324,000
YCH240E4HFA	TCI	460/3/60	240,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-410A
- Short orifice refrigerant control
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Sloped sheet metal drain pan
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

25 Ton
YCD300E

Downflow Packaged Gas/Electric

R-410

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD300E3L0A	—	208-230/3/60	272,000	203,000
YCD300E3LAA	Economizer	208-230/3/60	272,000	203,000
YCD300E3LFA	TCI	208-230/3/60	272,000	203,000
YCD300E3LGA	Econ/TCI	208-230/3/60	272,000	203,000
YCD300E3H0A	—	208-230/3/60	272,000	324,000
YCD300E3HAA	Economizer	208-230/3/60	272,000	324,000
YCD300E3HFA	TCI	208-230/3/60	272,000	324,000
YCD300E3HGA	Econ/TCI	208-230/3/60	272,000	324,000
YCD300E4L0A	—	460/3/60	272,000	203,000
YCD300E4LAA	Economizer	460/3/60	272,000	203,000
YCD300E4LFA	TCI	460/3/60	272,000	203,000
YCD300E4LGA	Econ/TCI	460/3/60	272,000	203,000
YCD300E4H0A	—	460/3/60	272,000	324,000
YCD300E4HAA	Economizer	460/3/60	272,000	324,000
YCD300E4HFA	TCI	460/3/60	272,000	324,000
YCD300E4HGA	Econ/TCI	460/3/60	272,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated downflow design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

25 Ton YCH300E

Horizontal Packaged Gas/Electric

R-410

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH300E3L0A	—	208-230/3/60	290,000	203,000
YCH300E3LFA	TCI	208-230/3/60	290,000	203,000
YCH300E3H0A	—	208-230/3/60	290,000	324,000
YCH300E3HFA	TCI	208-230/3/60	290,000	324,000
YCH300E4L0A	—	460/3/60	290,000	203,000
YCH300E4LFA	TCI	460/3/60	290,000	203,000
YCH300E4H0A	—	460/3/60	290,000	324,000
YCH300E4HFA	TCI	460/3/60	290,000	324,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Dedicated horizontal design
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Sloped sheet metal drain pan
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

12-1/2 Ton YCH151C

Horizontal Packaged Gas/Electric

High Efficiency

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH151C3L0B	—	208-230/3/60	154,000	122,000
YCH151C3LBB	Ov Motor	208-230/3/60	154,000	122,000
YCH151C3LFB	TCI	208-230/3/60	154,000	122,000
YCH151C3H0B	—	208-230/3/60	154,000	203,000
YCH151C3HBB	Ov Motor	208-230/3/60	154,000	203,000
YCH151C3HFB	TCI	208-230/3/60	154,000	203,000
YCH151C4L0B	—	460/3/60	154,000	122,000
YCH151C4LBB	Ov Motor	460/3/60	154,000	122,000
YCH151C4LFB	TCI	460/3/60	154,000	122,000
YCH151C4H0B	—	460/3/60	154,000	203,000
YCH151C4HBB	Ov Motor	460/3/60	154,000	203,000
YCH151C4HFB	TCI	460/3/60	154,000	203,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Short orifice refrigerant control
- High efficiency scroll compressors
- Low pressure switches
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Gas burner view port
- Sloped sheet metal drain pan
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

12-1/2 Ton
YCD151C
YFD151C

Downflow Packaged Gas/Electric

High Efficiency

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD151C3L0B	—	208-230/3/60	154,000	122,000
YCD151C3LAB	Economizer	208-230/3/60	154,000	122,000
YCD151C3LBB	Ov Motor	208-230/3/60	154,000	122,000
YCD151C3LCB	Econ/OvMtr	208-230/3/60	154,000	122,000
YCD151C3LFB	TCI	208-230/3/60	154,000	122,000
YCD151C3LGB	Econ/TCI	208-230/3/60	154,000	122,000
YCD151C3H0B	—	208-230/3/60	154,000	203,000
YCD151C3HAB	Economizer	208-230/3/60	154,000	203,000
YCD151C3HBB	Ov Motor	208-230/3/60	154,000	203,000
YCD151C3HCB	Econ/OvMtr	208-230/3/60	154,000	203,000
YCD151C3HFB	TCI	208-230/3/60	154,000	203,000
YCD151C3HGB	Econ/TCI	208-230/3/60	154,000	203,000
YCD151C4L0B	—	460/3/60	154,000	122,000
YCD151C4LAB	Economizer	460/3/60	154,000	122,000
YCD151C4LBB	Ov Motor	460/3/60	154,000	122,000
YCD151C4LCB	Econ/OvMtr	460/3/60	154,000	122,000
YCD151C4LFB	TCI	460/3/60	154,000	122,000
YCD151C4LGB	Econ/TCI	460/3/60	154,000	122,000
YCD151C4H0B	—	460/3/60	154,000	203,000
YCD151C4HAB	Economizer	460/3/60	154,000	203,000
YCD151C4HBB	Ov Motor	460/3/60	154,000	203,000
YCD151C4HCB	Econ/OvMtr	460/3/60	154,000	203,000
YCD151C4HFB	TCI	460/3/60	154,000	203,000
YCD151C4HGB	Econ/TCI	460/3/60	154,000	203,000

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

15 Ton
YCH181C

Horizontal Packaged Gas/Electric

High Efficiency

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH181C3L0C	—	208-230/3/60	189,000	203,000
YCH181C3LBC	Ov Motor	208-230/3/60	189,000	203,000
YCH181C3LFC	TCI	208-230/3/60	189,000	203,000
YCH181C3H0C	—	208-230/3/60	189,000	284,000
YCH181C3HBC	Ov Motor	208-230/3/60	189,000	284,000
YCH181C3HFC	TCI	208-230/3/60	189,000	284,000
YCH181C4L0C	—	460/3/60	189,000	203,000
YCH181C4LBC	Ov Motor	460/3/60	189,000	203,000
YCH181C4LFC	TCI	460/3/60	189,000	203,000
YCH181C4H0C	—	460/3/60	189,000	284,000
YCH181C4HBC	Ov Motor	460/3/60	189,000	284,000
YCH181C4HFC	TCI	460/3/60	189,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Low pressure switches
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Sloped sheet metal drain pan
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- **1-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

15 Ton
YCD181C
YFD181C

Downflow Packaged Gas/Electric

High Efficiency

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD181C3L0C	—	208-230/3/60	189,000	203,000
YCD181C3LAC	Economizer	208-230/3/60	189,000	203,000
YCD181C3LBC	Ov Motor	208-230/3/60	189,000	203,000
YCD181C3LCC	Econ/OvMtr	208-230/3/60	189,000	203,000
YCD181C3LFC	TCI	208-230/3/60	189,000	203,000
YCD181C3LGC	Econ/TCI	208-230/3/60	189,000	203,000
YCD181C3H0C	—	208-230/3/60	189,000	284,000
YCD181C3HAC	Economizer	208-230/3/60	189,000	284,000
YCD181C3HBC	Ov Motor	208-230/3/60	189,000	284,000
YCD181C3HCC	Econ/OvMtr	208-230/3/60	189,000	284,000
YCD181C3HFC	TCI	208-230/3/60	189,000	284,000
YCD181C3HGC	Econ/TCI	208-230/3/60	189,000	284,000
YCD181C4L0C	—	460/3/60	189,000	203,000
YCD181C4LAC	Economizer	460/3/60	189,000	203,000
YCD181C4LBC	Ov Motor	460/3/60	189,000	203,000
YCD181C4LCC	Econ/OvMtr	460/3/60	189,000	203,000
YCD181C4LFC	TCI	460/3/60	189,000	203,000
YCD181C4LGC	Econ/TCI	460/3/60	189,000	203,000
YCD181C4H0C	—	460/3/60	189,000	284,000
YCD181C4HAC	Economizer	460/3/60	189,000	284,000
YCD181C4HBC	Ov Motor	460/3/60	189,000	284,000
YCD181C4HCC	Econ/OvMtr	460/3/60	189,000	284,000
YCD181C4HFC	TCI	460/3/60	189,000	284,000
YCD181C4HGC	Econ/TCI	460/3/60	189,000	284,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

17-1/2 Ton YCH211C

Horizontal Packaged Gas/Electric

High Efficiency

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH211C3L0C	—	208-230/3/60	220,000	203,000
YCH211C3LBC	Ov Motor	208-230/3/60	220,000	203,000
YCH211C3LFC	TCI	208-230/3/60	220,000	203,000
YCH211C3H0C	—	208-230/3/60	220,000	284,000
YCH211C3HBC	Ov Motor	208-230/3/60	220,000	284,000
YCH211C3HFC	TCI	208-230/3/60	220,000	284,000
YCH211C4L0C	—	460/3/60	220,000	203,000
YCH211C4LBC	Ov Motor	460/3/60	220,000	203,000
YCH211C4LFC	TCI	460/3/60	220,000	203,000
YCH211C4H0C	—	460/3/60	220,000	284,000
YCH211C4HBC	Ov Motor	460/3/60	220,000	284,000
YCH211C4HFC	TCI	460/3/60	220,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Short orifice refrigerant control
- Liquid line drier
- Operating charge of R-22
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll scroll compressors
- Low pressure switches
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube heat exchanger
- Hot surface ignition system
- Aluminized steel drum material
- Forced combustion
- Sloped sheet metal drain pan
- Gas burner view port
- Negative pressure gas valve
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **5-year compressor and heat exchanger warranty**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

17-1/2 Ton YCD211C

Downflow Packaged Gas/Electric

High Efficiency

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD211C3L0C	—	208-230/3/60	220,000	203,000
YCD211C3LAC	Economizer	208-230/3/60	220,000	203,000
YCD211C3LBC	Ov Motor	208-230/3/60	220,000	203,000
YCD211C3LCC	Econ/OvMtr	208-230/3/60	220,000	203,000
YCD211C3LFC	TCI	208-230/3/60	220,000	203,000
YCD211C3LGC	Econ/TCI	208-230/3/60	220,000	203,000
YCD211C3H0C	—	208-230/3/60	220,000	284,000
YCD211C3HAC	Economizer	208-230/3/60	220,000	284,000
YCD211C3HBC	Ov Motor	208-230/3/60	220,000	284,000
YCD211C3HCC	Econ/OvMtr	208-230/3/60	220,000	284,000
YCD211C3HFC	TCI	208-230/3/60	220,000	284,000
YCD211C3HGC	Econ/TCI	208-230/3/60	220,000	284,000
YCD211C4L0C	—	460/3/60	220,000	203,000
YCD211C4LAC	Economizer	460/3/60	220,000	203,000
YCD211C4LBC	Ov Motor	460/3/60	220,000	203,000
YCD211C4LCC	Econ/OvMtr	460/3/60	220,000	203,000
YCD211C4LFC	TCI	460/3/60	220,000	203,000
YCD211C4LGC	Econ/TCI	460/3/60	220,000	203,000
YCD211C4H0C	—	460/3/60	220,000	284,000
YCD211C4HAC	Economizer	460/3/60	220,000	284,000
YCD211C4HBC	Ov Motor	460/3/60	220,000	284,000
YCD211C4HCC	Econ/OvMtr	460/3/60	220,000	284,000
YCD211C4HFC	TCI	460/3/60	220,000	284,000
YCD211C4HGC	Econ/TCI	460/3/60	220,000	284,000
YCH241C3L0C	—	208-230/3/60	268,000	203,000
YCH241C3LBC	Ov Motor	208-230/3/60	268,000	203,000
YCH241C3LFC	TCI	208-230/3/60	268,000	203,000
YCH241C3H0C	—	208-230/3/60	268,000	284,000
YCH241C3HBC	Ov Motor	208-230/3/60	268,000	284,000
YCH241C3HFC	TCI	208-230/3/60	268,000	284,000
YCH241C4L0C	—	460/3/60	268,000	203,000
YCH241C4LBC	Ov Motor	460/3/60	268,000	203,000
YCH241C4LFC	TCI	460/3/60	268,000	203,000

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

High Efficiency

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH241C4H0C	—	460/3/60	268,000	284,000
YCH241C4HBC	Ov Motor	460/3/60	268,000	284,000
YCH241C4HFC	TCI	460/3/60	268,000	284,000

Features:

- **ReliaTel™** controls
- Built in anti-short cycle, time-delay relay and minimum on time controls
- ICS compatibility with either factory or field installed Trane Communications Interface (TCI)
- Quick-adjust idler arm assembly for belt and motor sheave adjustment
- 2" throwaway filters
- Liquid line drier
- Operating charge of R-22
- Short orifice refrigerant control
- Fork lift channels
- Trane-Tite-Top (T3) weather tight top and cabinet
- Trane 3-D® scroll compressors
- Low pressure switches
- Dedicated horizontal and downflow designs
- Single side access
- Drum and tube gas heat exchanger
- Hot surface ignition system
- Forced combustion
- Gas burner view port
- Negative pressure gas valve
- Sloped sheet metal drain pan
- Quick-access panels with handles
- Internally enhanced coil tubing
- Low ambient cooling to 0° F standard
- Colored and numbered wiring
- UL listed and CSA certified
- **1-year compressor and heat exchanger warranty on 20 and 25 ton units**

TRANE

It's Hard To Stop A Trane.®

PAQUETES GAS/ELECTRIC

20 Ton
YCD241C
YFD241C

Downflow Packaged Gas/Electric

Specifications: Downflow — High Efficiency

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD241C3L0C	—	208-230/3/60	268,000	203,000
YCD241C3LAC	Economizer	208-230/3/60	268,000	203,000
YCD241C3LBC	Ov Motor	208-230/3/60	268,000	203,000
YCD241C3LCC	Econ/OvMtr	208-230/3/60	268,000	203,000
YCD241C3LFC	TCI	208-230/3/60	268,000	203,000
YCD241C3LGC	Econ/TCI	208-230/3/60	268,000	203,000
YCD241C3H0C	—	208-230/3/60	268,000	324,000
YCD241C3HAC	Economizer	208-230/3/60	268,000	324,000
YCD241C3HBC	Ov Motor	208-230/3/60	268,000	324,000
YCD241C3HCC	Econ/OvMtr	208-230/3/60	268,000	324,000
YCD241C3HFC	TCI	208-230/3/60	268,000	324,000
YCD241C3HGC	Econ/TCI	208-230/3/60	268,000	324,000
YCD241C4L0C	—	460/3/60	268,000	203,000
YCD241C4LAC	Economizer	460/3/60	268,000	203,000
YCD241C4LBC	Ov Motor	460/3/60	268,000	203,000
YCD241C4LCC	Econ/OvMtr	460/3/60	268,000	203,000
YCD241C4LFC	TCI	460/3/60	268,000	203,000
YCD241C4LGC	Econ/TCI	460/3/60	268,000	203,000
YCD241C4H0C	—	460/3/60	268,000	324,000
YCD241C4HAC	Economizer	460/3/60	268,000	324,000
YCD241C4HBC	Ov Motor	460/3/60	268,000	324,000
YCD241C4HCC	Econ/OvMtr	460/3/60	268,000	324,000
YCD241C4HFC	TCI	460/3/60	268,000	324,000
YCD241C4HGC	Econ/TCI	460/3/60	268,000	324,000

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

25 Ton
YCH301C
YCD301C

Horizontal and Downflow Packaged Gas/Electric

High Efficiency

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCH301C3L0C	—	208-230/3/60	300,000	203,000
YCH301C3LFC	TCI	208-230/3/60	300,000	203,000
YCH301C3H0C	—	208-230/3/60	300,000	324,000
YCH301C3HFC	TCI	208-230/3/60	300,000	324,000
YCH301C4L0C	—	460/3/60	300,000	203,000
YCH301C4LFC	TCI	460/3/60	300,000	203,000
YCH301C4H0C	—	460/3/60	300,000	324,000
YCH301C4HFC	TCI	460/3/60	300,000	324,000

Specifications: Downflow

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD301C3L0C	—	208-230/3/60	300,000	203,000
YCD301C3LAC	Economizer	208-230/3/60	300,000	203,000
YCD301C3LFC	TCI	208-230/3/60	300,000	203,000
YCD301C3LGC	Econ/TCI	208-230/3/60	300,000	203,000
YCD301C3H0C	—	208-230/3/60	300,000	324,000
YCD301C3HAC	Economizer	208-230/3/60	300,000	324,000
YCD301C3HFC	TCI	208-230/3/60	300,000	324,000
YCD301C3HGC	Econ/TCI	208-230/3/60	300,000	324,000
YCD301C4L0C	—	460/3/60	300,000	203,000
YCD301C4LAC	Economizer	460/3/60	300,000	203,000
YCD301C4LFC	TCI	460/3/60	300,000	203,000
YCD301C4LGC	Econ/TCI	460/3/60	300,000	203,000

PAQUETES GAS/ELECTRIC

It's Hard To Stop A Trane.®

25 Ton
YCH301C
YCD301C

Horizontal and Downflow Packaged Gas/Electric

High Efficiency

Specifications: Horizontal

Model Number	Factory Installed Option	Power Supply	Gross Capacity Cooling (BTUH)	Capacity Heating Output (BTUH)
YCD301C4H0C	—	460/3/60	300,000	324,000
YCD301C4HAC	Economizer	460/3/60	300,000	324,000
YCD301C4HFC	TCI	460/3/60	300,000	324,000
YCD301C4HGC	Econ/TCI	460/3/60	300,000	324,000